

## **Dimensions and Performance**

Undercarriage		
Crawler width	180 mm	
Bottom rollers for side	3	
• Idler	spring-release with greased tensioner	
• Brake	negative, integrate in drive gearboxes	
Dimensions		
Max length (transport layout)	1934 mm, closed platform	
Max width (transport layout)	758 mm	
Machine height	1330 mm	
Max unloading height	450 mm	
Performance		
Max Drive speed	first 2 km/h / second 4 km/h	
Max gradability	15°	
Capacity	truck volume 0.28 m <sup>3</sup>	
Rated volume	0.34 m <sup>3</sup>	
Max skip capacity	700 kg	
Safety Standards (Conformity Assessment)		
• EN 474-1 / EN474-6		
Ergonomics of the controls		
<ul> <li>An ignition and safety key protects the r</li> </ul>	nachine	
<ul> <li>Moving the dumper is done with the right</li> </ul>	ht hand	
A sensor on the controls, avoids all involuntary movements		
The machine is equipped with two speeds		
The movement of the vessel is carried out with a lever		
A horn is present on the dashboard		
Note		

In general, the performance and dimensions are similar to the petrol or diesel equivalent model.

# **Battery Pack Technology**

Model name	KC70-4e
Closed modules, plug and play	
• 44V 126Ah for 4,4kwh	
New Technology LiMnCo (Nickel / Manganese / Cobalt)	
High Stability discharge	
Low weight, and high energy density	
Long life 3000 cycles	
• DOD 80%	
Automatic heater system	
The battery allows the machine to work a full day.	
We have a UBC (Universal fast external Battery Charger) sold with the machine, this works with the following power and tensions (3Kw and from 80V to 240V).	
The battery recharges to 80% in 1.5 hours with its charger (supplied) in a standard 3kW socket.	

The battery is 100% charged and does complete cell balancing in 3 hours with its charger.

### **Motor Technology**

Model name	KC70-4e
IPM technology (Interior Permanent Magnet)	
• 48V AC	
• 300 A peak	
• 4000 rpm	
With brake	
• IP67	
High Efficiency	
High Reliability	

Interior Permanent Magnet AC motors are more compact of traditional induction motors and have more than 94% efficiency.

This engine can work in humid conditions without any problems.

#### **Service and Maintenance**

Model name	KC70-4e
NO MAINTENANCE need for motor, battery and inverter.	
A simple and clear diagnostic system is installed as standard.	
The charger is sold with the machine.	

★ Specifications are subject to change without notice for purpose of improveme. All images shown are for brochure purposes only.



#### **KUBOTA EUROPE S.A.S.**

19 rue Jules Vercruysse Zone Industrielle - CS 50088 95101 Argenteuil Cedex France Téléphone : (33) 01 34 26 34 34 Télécopieur : (33) 01 34 26 34 99 www.kubota-eu.com

# For Earth, For Life